

	$h_t$ [mm]	$t$ [mm]	$s$ [mm]	$h_s$ [mm]
<b>MXL</b>	0,51	2,032	1,14	1,20
<b>XL</b>	1,27	5,080	2,57	2,30
<b>L</b>	1,91	9,525	4,65	3,60
<b>H</b>	2,29	12,700	6,12	4,30

Cuerda de tracción de fibra de vidrio			Cable de tracción de acero		
Referencia correa	Anchura [mm]	Long. de rollo [m]	Referencia correa	Anchura [mm]	Long. de rollo [m]
MXL 025	6,35	30	H 050 - St	12,70	30
XL 025	6,35	30	H 075 - St	19,05	30
XL 031	7,94	30	H 100 - St	25,40	30
XL 037	9,53	30	H 150 - St	38,10	30
XL 050	12,70	30	H 200 - St	50,80	30
L 037	9,53	30			
L 050	12,70	30			
L 075	19,05	30			
L 100	25,40	30			
H 050	12,70	30			
H 075	19,05	30			
H 100	25,40	30			
H 150	38,10	30			
H 200	50,80	30			

	$h_t$ [mm]	$t$ [mm]	$h_s$ [mm]
<b>3M</b>	1,1	3	2,3
<b>5M</b>	1,9	5	3,4
<b>8M</b>	3,2	8	5,4
<b>14M</b>	5,6	14	9,5

Cuerda de tracción de fibra de vidrio			Cable de tracción de acero		
Referencia correa	Anchura [mm]	Long. de rollo [m]	Referencia correa	Anchura [mm]	Long. de rollo [m]
8M 30	30,0	30	5M 06 - St	6,0	30
8M 50	50,0	30	5M 09 - St	9,0	30
8M 85	85,0	30	5M 15 - St	15,0	30
14M 25	25,0	30	5M 25 - St	25,0	30
14M 40	40,0	30	8M 10 - St	10,0	30
14M 55	55,0	30	8M 15 - St	15,0	30
14M 85	85,0	30	8M 20 - St	20,0	30
			8M 30 - St	30,0	30
			8M 50 - St	50,0	30
			8M 85 - St	85,0	30
			14M 25 - St	25,0	30
			14M 40 - St	40,0	30
			14M 55 - St	55,0	30
			14M 85 - St	85,0	30